

PRODUCT : MICRON BLOCK
REF. NO. : MIC02

DOC. NO.	QF/RD/05
ISSUE	01
REVISION	00
DATE	28-05-2014

CONFORMING TO EN 360:2002



1	PHYSICAL PARAMETERS	GENERAL		<ul style="list-style-type: none"> • Robust and Durable Plastic Casing. • Swivel Steel Snap hook PN 162 with load indicator at attachment end. • Ø16 mm Swivel eye at the anchorage end. • Comes with 21 mm wide webbing. • Inbuilt textile energy absorber. • Maximum length: 2 meter • Side dimensions: 87.4 mm X 55.6 mm x 101.6 mm.
			WEIGHT	600 gm ± 10 gm (excluding the weight of PN 162)
2	TEXTILE COMPONENTS	WEBBING	MATERIAL WIDTH BREAKING STRENGTH	Polyester 21 mm ± 1 mm 20 kN (Min.)
3	METALLIC ASSEMBLY	SWIVEL STEEL SNAP HOOK PN 162	MATERIAL BREAKING STRENGTH FINISH	Alloy steel 25 kN (Min.) Galvanized with golden yellow/ silver passivation
4	VITAL TEST COMPLIANCE	STATIC STRENGTH		When subjected to a static force of 15 kN for 3 Min., the assembly of the block and the lanyard shows no sign of any damage or fracture.
		DYNAMIC PERFORMANCE		When subjected to a fall with a rigid mass of 100 Kg, the breaking force is less than 6 kN, and the arrest distance is less than 2 m.



SUCCESS UDYOG PVT. LTD.

Registered Office: Office No. 315/316, 3rd floor, City Space, Sr.No.198/1A,
Pune Nagar Road, Pune 411014, Maharashtra

Godown : Jadhav warehousing, Gat no. 1338/1, Priyankanagari, Wagholi, Pune – 411207

Off. Tel: 020-40188288/216/244/221-228, Cell-9371919702/9370223873 Fax: 020-40188227/299

Email: sales@successudyog.com Web: www.successudyog.com

